



FORMATI
SIZE FORMATS FORMSTUKE FORMATES



90x90 - 36"x36" NAT RT *




14,7x90 - 6"x36" NAT RT *



60x120 - 24"x48" NAT RT *



30x120 - 12"x48" NAT RT *



60x60 - 24"x24" NAT RT *



14,7x60 - 6"x24" NAT RT *

COLORI
COLORS COULEURS FARBEN COLORES



SUGAR



CAMEL



ARKI



LAVA

DECORI
DECORS DECORATIONS DEKORE DECOROS



LINES MULTISPESSORE
30x120 - 12"x48" NAT RT *

Da posare senza stuccatura.
To be installed without grouting.
À poser sans mastic.
Ohne Ausfugung zu verlegen.
Colocación sin masilla.



STRIPS
30x60 - 12"x24" NAT RT *

* Disponibile in tutti i colori . Available in all the colours . Disponible dans tous les couleurs . In allen farben in der erhältlich . Disponible en todos los colores

CARATTERISTICHE TECNICHE - PIASTRELLE PRESSATE A SECCO - CONFORME ALLA NORMA EN 14411
APPENDICE G GRUPPO BIa

TECHNICAL FEATURES - DRY PRESSED TILES - COMPLIANT WITH STANDARDS EN 14411 ANNEX G GROUP BIa

		CARATTERISTCA TECNICA TECHNICAL FEATURES	NORMA SPECIFICATION	VALORE PRESCRITTO VALUES REQUIRED	*VALORE KEOPE *KEOPE VALUES
CARATTERISTICHE STRUTTURALI STRUCTURAL CHARACTERISTICS		ASSORBIMENTO D'ACQUA WATER ABSORPTION	ISO 10545-3	≤ 0,5 %	CONFORME IN ACCORDANCE
		FORZA DI ROTTURA BREAKING STRENGHT	ISO 10545-4	≥ 700 N	CONFORME IN ACCORDANCE
		MODULO DI ROTTURA MODULUS OF RUPTURE		≥ 35 N/mm²	CONFORME IN ACCORDANCE
CARATTERISTICHE SUPERFICIALI SURFACE CHARACTERISTICS		RESISTENZA ALLA ABRASIONE PROFONDA RESISTANCE TO DEEP ABRASION	ISO 10545-6	≤ 175 mm³	CONFORME IN ACCORDANCE
CARATTERISTICHE TERMO IGROMETRICHE THERMAL AND HYGROMETRIC CHARACTERISTICS	 	RESISTENZA AGLI SBALZI TERMICI THERMAL SHOCK RESISTANCE	ISO 10545-9	METODO DI PROVA DISPONIBILE TEST METHOD AVAILABLE	GARANTITA GUARANTEED
		RESISTENZA AL GELO FROST RESISTANCE	ISO 10545-12	RICHIESTA REQUIRED	GARANTITA GUARANTEED
CARATTERISTICHE CHIMICHE CHEMICAL CHARACTERISTICS	 	RESISTENZA AI PRODOTTI CHIMICI CHEMICAL RESISTANCE	ISO 10545-13	METODO DI PROVA DISPONIBILE TEST METHOD AVAILABLE	GARANTITA (NAT) GUARANTEED (NAT)
		RESISTENZA ALLE MACCHIE RESISTANCE TO STAINING	ISO 10545-14	METODO DI PROVA DISPONIBILE TEST METHOD AVAILABLE	GARANTITA (NAT) GUARANTEED (NAT)
CARATTERISTICHE DI SICUREZZA SAFETY CHARACTERISTICS		COEFFICIENTE DI ATTRITO DINAMICO DYNAMIC SLIDER	BCRA	METODO DI PROVA DISPONIBILE TEST METHOD AVAILABLE	> 0,4
		COEFFICIENTE DI ATTRITO STATICO STATIC SLIDER	ASTM C1028		
		CLASSIFICAZIONE ANTISDRUCCIOLO INCLINED PLATFORM	DIN 51130		R9
			DIN 51097		A

*VALORI MEDI RIFERITI A PROVE FATTE NEGLI ULTIMI 24 MESI - AVARAGE VALUES REFER TO TEST DONE IN THE PREVIOUS 24 MONTHS

"W" MISURA DI FABBRICAZIONE - WORKING SIZE:
596x1195 . 297x1195 . 895x895 . 596x596 . 147x895. 147x596

VALORI "W" RIFERITI AI CALIBRI DI PRODUZIONE: 60x120 (6), 30x120 (6), 90x90 (5), 60x60 (6), 14,7x90 (5), 14,7x60 (6).
VALUES "W" RELATED TO THE PRODUCTION CALIPERS: 60x120 (6), 30x120 (6), 90x90 (5), 60x60 (6), 14,7x90 (5), 14,7x60 (6).

MISURE, PESI ED IMBALLI

SIZE, WEIGHT AND PACKAGING . FORMAT, POIDS CONDITIONNEMENT EMBALAJES MASSE . GEWICHT UND VERPACKUNG . MEDIDAS,
PESOS Y EMBALAJES

FORMATO size format formatos	spessore	PZ/SCATOLA pieces/box pièces/bôte stück/karton pzas/caja	MQ/SCATOLA mq/box mq/bôte mq/karton mq/caja	KG/SCATOLA kg/box kg/bôte kg/karton kg/caja	MQ/PALLET mq/pallet mq/pallet mq/pallet mq/pallet	KG/PALLET kg/pallet kg/pallet kg/pallet kg/pallet	SCATOLA/PALLET box/pallet bôte/pallet karton/pallet caja/pallet
60x120	4,8 mm	4	2,88	≈ 32,40	46,08	≈ 538,40	16
30x120	4,8 mm	8	2,88	≈ 33,16	46,08	≈ 550,56	16
90x90	4,8 mm	1	0,81	≈ 8,84	40,50	≈ 462,00	50
60x60	4,8 mm	6	2,16	≈ 24,52	86,40	≈ 1000,80	40
14,7x90	4,8 mm	18	2,12	≈ 27,00	-	-	-
14,7x60	4,8 mm	24	2,38	≈ 27,60	-	-	-

FORMATI
SIZE . FORMATS . FORMSTÜKE . FORMATES

	60x120 NAT RT	30x120 NAT RT	90x90 NAT RT	60x60 NAT RT	14,7x90 NAT RT	14,7x60 NAT RT
Arki	■	■	■	■	■	■
Caramel	■	■	■	■	■	■
Lava	■	■	■	■	■	■
Sugar	■	■	■	■	■	■

e-Ceramica
Contact us for wholesale prices or cooperation:
Zoran Milić
E-mail: info@e-ceramica.com

Mobile : + 386 41 684 696
Telephone : + 386 2 780 54 90
Fax : + 386 2 779 76 61

Merilly d.o.o. ; Vodnikova ulica 2 ; Si 2250 Ptuj ; Slovenia ; EU

Web : · Americas

[Ceramic tiles in Argentina](#)
[Ceramic tiles in Bahamas](#)
[Ceramic tiles in Bolivia](#)
[Ceramic tiles in Canada](#)
[Ceramic tiles in Chile](#)
[Ceramic tiles in Colombia](#)
[Ceramic tiles in Costa Rica](#)
[Ceramic tiles in Cuba](#)
[Ceramic tiles in Ecuador](#)
[Ceramic tiles in El Salvador](#)
[Ceramic tiles in Guatemala](#)
[Ceramic tiles in Honduras](#)
[Ceramic tiles in Jamaica](#)
[Ceramic tiles in México](#)
[Ceramic tiles in Nicaragua](#)
[Ceramic tiles in Panamá](#)
[Ceramic tiles in Paraguay](#)
[Ceramic tiles in Perú](#)
[Ceramics in Re. Dominicana](#)
[Ceramics in Trin. & Tobago](#)
[Ceramic tiles in Uruguay](#)
[Ceramic tiles in USA](#)
[Ceramic tiles in Venezuela](#)

· Europe

[Ceramic tiles in BIH](#)
[Ceramic tiles in Crna Gora](#)
[Ceramic tiles in España](#)
[Ceramic tiles in France](#)
[Ceramic tiles in Germany](#)
[Ceramic tiles in Hrvatska](#)
[Ceramic tiles in Ireland](#)
[Ceramic tiles in Kosove](#)
[Ceramic tiles in Liechtenstein](#)
[Ceramic tiles in Magyarország](#)
[Ceramic tiles in Македонија](#)
[Ceramic tiles in Maqedoni](#)
[Ceramic tiles in Malta](#)
[Ceramic tiles in Österreich](#)
[Ceramic tiles in Russia](#)
[Ceramic tiles in Schweiz](#)
[Ceramic tiles in Suisse](#)
[Ceramic tiles in Shqiperi](#)
[Ceramic tiles in Slovenija](#)
[Ceramic tiles in Србија](#)
[Ceramics in United Kingdom](#)

· Asia

[Ceramic tiles in India](#)
[Ceramic tiles in Pakistan](#)
[Ceramic tiles in Philippines](#)
[Ceramic tiles in Singapore](#)
[Ceramic tiles in Turkiye](#)

· Africa & Australia

[Ceramic tiles in Australia](#)
[Ceramic tiles in Cameroon](#)
[Ceramic tiles in Ghana](#)
[Ceramics in Guinea Ecuatorial](#)
[Ceramic tiles in Swaziland](#)
[Ceramic tiles in New Zealand](#)
[Ceramic tiles in Nigeria](#)