



PO

80.8

SlimmKer



79,1 x 79,1 RECT cm Φ 5,7 mm
31,14" x 31,14" RECT



59 x 118,4 RECT cm Φ 5,7 mm
23,23" x 46,61" RECT



29,4 x 118,4 RECT cm Φ 5,7 mm
11,57" x 46,61" RECT



19,2 x 118,4 RECT cm Φ 5,7 mm
7,56" x 46,61" RECT


Blanco	SK 88480	303	SK 120430	304	SK 120432	317	SK 120433	305
Piedra	SK 88510	303	SK 120540	304	SK 120542	317	SK 120543	305
Camel	SK 88490	303	SK 120440	304	SK 120442	317	SK 120443	305
Gris	SK 88520	303	SK 120550	304	SK 120552	317	SK 120553	305
Negro	SK 88500	303	SK 120450	304	SK 120452	317	SK 120453	305

SlimmKer - Floor

79,1 x 79,1 RECT cm Φ 5,7 + F* mm
31,14" x 31,14" RECT

59 x 118,4 RECT cm Φ 5,7 + F* mm
23,23" x 46,61" RECT

Blanco	SKF 88480	421	SKF 120430	428
Piedra	SKF 88510	421	SKF 120540	428
Camel	SKF 88490	421	SKF 120440	428
Gris	SKF 88520	421	SKF 120550	428
Negro	SKF 88500	421	SKF 120450	428



* El espesor de las referencias SKF (SlimmKer-Floor) es el equivalente a la suma del producto SK más la aplicación Floor.
* The thickness of SFK (SlimmKer-Floor) products is equivalent to the sum of the thickness of the SK product plus that of the Floor backing material.



PO

80.8

SlimmKer



11 x 118,4 RECT cm **ƒ 5,7 mm**
4,33" x 46,61" RECT



50 x 100 RECT cm **ƒ 4,3 mm**
19,69" x 39,37" RECT



33 x 33 cm
12,99" x 12,99"



31 x 29 cm
12,20" x 11,42"

- Blanco
- Piedra
- Camel
- Gris
- Negro
- Blanco - Gris - Negro
- Blanco - Piedra - Camel

SK 120434	318
SK 120544	318
SK 120444	318
SK 120554	318
SK 120454	318

SK 50510	424
SK 50520	424
SK 50530	424
SK 50540	424
SK 50550	424

SK 508	329
SK 538	329
SK 518	329
SK 548	329
SK 528	329
SK 507	329
SK 506	329


SK 509	330
SK 539	330
SK 519	330
SK 549	330
SK 529	330

SlimmKer - Floor

50 x 100 RECT cm **ƒ 4,3 + F* mm**
19,69" x 39,37" RECT

- Blanco
- Piedra
- Camel
- Gris
- Negro

SKF 50510	429
SKF 50520	429
SKF 50530	429
SKF 50540	429
SKF 50550	429



* El espesor de las referencias SKF (SlimmKer-Floor) es el equivalente a la suma del producto SK más la aplicación Floor.
* The thickness of SKF (SlimmKer-Floor) products is equivalent to the sum of the thickness of the SK product plus that of the Floor backing material.



PO

80.8




80 x 80 CL cm **ƒ 11,5 mm**
31,50" x 31,50" CL



60 x 60 CL cm **ƒ 10 mm**
23,62" x 23,62" CL

Blanco	P-88480 CL	290	P-68380 CL	291
Piedra	P-88510 CL	184	P-68410 CL	180
Camel	P-88490 CL	183	P-68390 CL	179
Gris	P-88520 CL	183	P-68420 CL	179
Negro	P-88500 CL	184	P-68400 CL	180



BLANCO



PIEDRA



CAMEL



GRIS



NEGRO



PO

80.8

Piezas especiales / Special pieces

SlimmKer



9,5 x 79,1 cm

Blanco	RODSK-88480	728
Piedra	RODSK-88510	728
Camel	RODSK-88490	728
Gris	RODSK-88520	728
Negro	RODSK-88500	728



79,1 x 79,1 cm

PTISKF-88480	725
PTISKF-88510	725
PTISKF-88490	725
PTISKF-88520	725
PTISKF-88500	725



79,1 x 79,1 cm

ATISKF-88480	726
ATISKF-88510	726
ATISKF-88490	726
ATISKF-88520	726
ATISKF-88500	726

9,5 x 118,4 cm

Blanco	RODSK-120430	727
Piedra	RODSK-120540	727
Camel	RODSK-120440	727
Gris	RODSK-120550	727
Negro	RODSK-120450	727

59 x 118,4 cm

PTISKF-120430	723
PTISKF-120540	723
PTISKF-120440	723
PTISKF-120550	723
PTISKF-120450	723

59 x 118,4 cm

ATISKF-120430	724
ATISKF-120540	724
ATISKF-120440	724
ATISKF-120550	724
ATISKF-120450	724

9,5 x 100 cm

Blanco	RODSK-50510	718
Piedra	RODSK-50520	718
Camel	RODSK-50530	718
Gris	RODSK-50540	718
Negro	RODSK-50550	718

50 x 100 cm

PTISKF-50510	721
PTISKF-50520	721
PTISKF-50530	721
PTISKF-50540	721
PTISKF-50550	721

50 x 100 cm

ATISKF-50510	722
ATISKF-50520	722
ATISKF-50530	722
ATISKF-50540	722
ATISKF-50550	722




PO

80.8


Piezas especiales / Special pieces




9,5 x 80 cm



80 x 80 cm



80 x 80 cm



80 x 80 cm

Blanco	ROD-88480 CL	613	PR-88480 CL	615	PTI-88480 CL	683	ATI-88480 CL	693
Piedra	ROD-88510 CL	613	PR-88510 CL	615	PTI-88510 CL	683	ATI-88510 CL	693
Camel	ROD-88490 CL	613	PR-88490 CL	615	PTI-88490 CL	683	ATI-88490 CL	693
Gris	ROD-88520 CL	613	PR-88520 CL	615	PTI-88520 CL	683	ATI-88520 CL	693
Negro	ROD-88500 CL	613	PR-88500 CL	615	PTI-88500 CL	683	ATI-88500 CL	693
<hr/>								
	8 x 60 cm		60 x 60 cm		60 x 60 cm		60 x 60 cm	
Blanco	ROD-68380 CL	621	PR-68380 CL	622	PTI-68380 CL	623	ATI-68380 CL	624
Piedra	ROD-68410 CL	621	PR-68410 CL	622	PTI-68410 CL	623	ATI-68410 CL	624
Camel	ROD-68390 CL	621	PR-68390 CL	622	PTI-68390 CL	623	ATI-68390 CL	624
Gris	ROD-68420 CL	621	PR-68420 CL	622	PTI-68420 CL	623	ATI-68420 CL	624
Negro	ROD-68400 CL	621	PR-68400 CL	622	PTI-68400 CL	623	ATI-68400 CL	624



PO

80.8

Características técnicas según normas / Technical characteristics
 Caractéristiques techniques selon les normes / Vorschriftenmäßige technische Eigenschaften / Технические характеристики согласно стандартам

ISO 13006:1998 / GRUPO Bla UNE - EN 14411:2003 / GRUPO Bla	Características técnicas según normas: Technical characteristics:	Norma de referencia Reference standard	Valor requerido Value required	Valor medio obtenido Mean value
Características dimensionales Dimensional characteristics Caractéristiques dimensionnelles Abmessungen Размерные характеристики	Longitud y anchura Length and width - Longueur et largeur - Länge und Breite - Длина и ширина	EN-ISO 10545-2	± 0,5 %	± 0,5 %
	Grosor Thickness - Épaisseur - Dicke - Толщина	EN-ISO 10545-2	± 5 %	± 5 %
	Rectitud de los lados Warpages of edges - Rectitude des côtés - Kantengeradheit - Выровненность бортов	EN-ISO 10545-2	± 0,5 %	± 0,5 %
	Ortogonalidad Wedging - Orthogonalité - Rechtwinkligkeit - Прямоугольность	EN-ISO 10545-2	± 0,6 %	± 0,5 %
	Planaridad Flatness - Planéité - Ebenflächigkeit - Плоскостность	EN-ISO 10545-2	± 0,5 %	± 0,5 %
Características físicas Physical characteristics Caractéristiques physiques Physikalische Eigenschaften Физические характеристики	Absorción al agua Water adsorption - Absorption d'eau - Wasseraufnahme - Влагопоглощение	EN-ISO 10545-3	≤ 0,5 %	≤ 0,2 %
	Fuerza de rotura Breaking strength - Force de rupture - Bruchkraft - Сила разрыва	EN-ISO 10545-4	≥ 1.300 N	≥ 3.000 N
	Resistencia a la flexión Bending strength - Résistance à la flexion - Biegefestigkeit - Сопротивление изгибу	EN-ISO 10545-4	≥ 35 N / mm ²	≥ 40 N / mm ²
	Resistencia a la abrasión profunda Resistance to deep abrasion - Résistance à l'abrasion profonde - Widerstandsfähigkeit gegen Tiefenabrieb - Сопротивление глубокому истиранию	EN-ISO 10545-6	≤ 175 mm ³	≤ 135 mm ³
	Resistencia a la abrasión Resistance to abrasion utility - Résistance à l'abrasion - Abriebfestigkeit - Сопротивление истиранию	EN-ISO 10545-7	Indicada por el fabricante As indicated by manufacturer Indiquée par le fabricant Herstellerangaben Указанное производителем	3 - 5
	Dilatación Térmica lineal Lineal thermal expansion - Dilatation thermique linéaire Lineare Wärmedehnung - Линейное тепловое расширение	EN-ISO 10545-8	Método disponible Method available Méthode disponible Verfügbares Verfahren Имеющаяся методика	≤ 9 x 10 ⁻⁶ K ⁻¹
	Resistencia al choque térmico Thermal shock resistance - Résistance au choc thermique - Beständigkeit gegen Temperaturschwankungen - Устойчивость к резким перепадам температуры	EN-ISO 10545-9	Método disponible Method available Méthode disponible Verfügbares Verfahren Имеющаяся методика	Resiste Resist - Résiste Beständig - Да
	Dureza Mohs Mohs surface hardness - Dureté Mohs - Härte auf der Mohs - Твердость по Моосу	EN 101	-	8
Resistencia a la helada Frost resistance - Résistance au gel - Frostbeständigkeit - Морозоустойчивость	EN-ISO 10545-12	Exigida - Required - Requis Erfordert - Требуемая	Resiste Resist - Résiste Beständig - Да	
Características químicas Chemical characteristics Caractéristiques chimiques Chemische Eigenschaften Химические характеристики	Resistencia a productos domésticos de limpieza y aditivos de piscina Resistance to household cleaning products and swimming pool additives Résistance aux produits ménagers de nettoyage et aux aditifs pour piscines Beständigkeit gegen Haushaltsreiniger und Schwimmbadzusätze Устойчивость к воздействию бытовых чистящих средств и добавок для бассейна	EN-ISO 10545-13	Mín. GB - GB min. Min. GB - Min. GB мин. GB	Resiste (GA) - Resist (GA) - Résiste (GA) -Beständig (GA) - Да (GA)
	Resistencia a ácidos y bases en baja concentración Resistance to acids and bases in low concentration Résistance aux acides et bases à faibles concentrations Beständigkeit gegen Säuren und Laugen in geringer Konzentration Устойчивость к воздействию кислот и щелочей низкой концентрации	EN-ISO 10545-13	Indicada por el fabricante As indicated by manufacturer Indiquée par le fabricant Herstellerangaben Указанное производителем	Resiste (GLA) - Resist (GLA) - Résiste (GLA) -Beständig (GLA) - Да (GLA)
	Resistencia a las manchas Resistance to staining - Résistance aux taches - Fleckenbeständigkeit - Сопротивление пятнообразованию	EN-ISO 10545-14	Mín. Clase 3 - Class 3 min. Min. Klasse 3 - Min. Klasse 3 мин. Класс 3	Clase 5 - Class 5 Classe 5 - Klasse 5 Класс 5

Estas características son aplicables únicamente al 80.8 de espesor tradicional. - These characteristics apply exclusively to the standard thickness 80.8 model.
 Ces caractéristiques ne sont valables que pour le modèle 80.8 d'épaisseur traditionnelle. - Diese Merkmale gelten ausschließlich für das Model 80.8 mit herkömmlicher Dicke.
 Эти характеристики применимы исключительно к модели 80.8 со стандартной толщиной

e-Ceramica

Contact us for wholesale prices or cooperation:

Zoran Milić

E-mail: info@e-ceramica.com

Mobile : + 386 41 684 696

Telephone : + 386 2 780 54 90

Fax : + 386 2 779 76 61

Merilly d.o.o. ; Vodnikova ulica 2 ; Si 2250 Ptuj ; Slovenia ; EU

Web : · Americas

[Ceramic tiles in Argentina](#)
[Ceramic tiles in Bahamas](#)
[Ceramic tiles in Bolivia](#)
[Ceramic tiles in Canada](#)
[Ceramic tiles in Chile](#)
[Ceramic tiles in Colombia](#)
[Ceramic tiles in Costa Rica](#)
[Ceramic tiles in Cuba](#)
[Ceramic tiles in Ecuador](#)
[Ceramic tiles in El Salvador](#)
[Ceramic tiles in Guatemala](#)
[Ceramic tiles in Honduras](#)
[Ceramic tiles in Jamaica](#)
[Ceramic tiles in México](#)
[Ceramic tiles in Nicaragua](#)
[Ceramic tiles in Panamá](#)
[Ceramic tiles in Paraguay](#)
[Ceramic tiles in Perú](#)
[Ceramics in Re. Dominicana](#)
[Ceramics in Trin. & Tobago](#)
[Ceramic tiles in Uruguay](#)
[Ceramic tiles in USA](#)
[Ceramic tiles in Venezuela](#)

· Europe

[Ceramic tiles in BIH](#)
[Ceramic tiles in Crna Gora](#)
[Ceramic tiles in España](#)
[Ceramic tiles in France](#)
[Ceramic tiles in Germany](#)
[Ceramic tiles in Hrvatska](#)
[Ceramic tiles in Ireland](#)
[Ceramic tiles in Kosove](#)
[Ceramic tiles in Liechtenstein](#)
[Ceramic tiles in Magyarország](#)
[Ceramic tiles in Македонија](#)
[Ceramic tiles in Maqedoni](#)
[Ceramic tiles in Malta](#)
[Ceramic tiles in Österreich](#)
[Ceramic tiles in Russia](#)
[Ceramic tiles in Schweiz](#)
[Ceramic tiles in Suisse](#)
[Ceramic tiles in Shqiperi](#)
[Ceramic tiles in Slovenija](#)
[Ceramic tiles in Србија](#)
[Ceramics in United Kingdom](#)

· Asia

[Ceramic tiles in India](#)
[Ceramic tiles in Pakistan](#)
[Ceramic tiles in Philippines](#)
[Ceramic tiles in Singapore](#)
[Ceramic tiles in Turkiye](#)

· Africa & Australia

[Ceramic tiles in Australia](#)
[Ceramic tiles in Cameroon](#)
[Ceramic tiles in Ghana](#)
[Ceramics in Guinea Ecuatorial](#)
[Ceramic tiles in Swaziland](#)
[Ceramic tiles in New Zealand](#)
[Ceramic tiles in Nigeria](#)