



# ANTISLIP

## VIDREPUR'S ANTI-SLIP FINISHING

NEW INTERNATIONAL BUILDING REGULATIONS PAY GREAT ATTENTION TO SAFETY REGARDING THE RISK OF FALLS. AT VIDREPUR OUR COLLECTIONS ALL HAVE AN ANTI-SLIP FINISHING, GUARANTEEING MAXIMUM SAFETY AND COMPLYING WITH REQUIREMENTS IN THE REGULATIONS, WHILST OFFERING THE WIDE RANGE OF COLORS THAT CHARACTERIZES OUR CATALOGUE.

AT VIDREPUR WE WORK WITH TWO TYPES OF ANTI-SLIP FINISHING, DEPENDING ON THE REQUIREMENTS: ANTI-SLIP CLASS 2 AND ANTI-SLIP CLASS 3



## FINISHINGS AND CHARACTERISTICS

FINISHING	SURFACE	COLOR
ANTI-SLIP CLASS 2	ROUGH BUT WITH A SATIN FINISH	NOT ALTERED FOG
ANTI-SLIP CLASS 3	ROUGH	WHEN DRY: THE ORIGINAL COLOR IS ALTERED WHEN WET: RECOVERS ITS ORIGINAL COLOR

\* THE LIGHTER THE ORIGINAL COLOR, THE LESS THE CHANGE IN TONE CAN BE APPRECIATED

\* TO GET AN ANTI-SLIP FINISHING THE MICRO-ROUGHNESS OF THE SURFACE MUST INCREASE. THE GREATER THE MICRO-ROUGHNESS, THE HIGHER THE DEGREE OF ANTI-SLIP, ALTHOUGH THE LEVEL OF MAINTENANCE OF THE PRODUCT ALSO INCREASES.

HOW TO CHOOSE THE CORRECT VIDREPUR ANTI-SLIP FINISHING?

THE FOLLOWING SHOULD BE BORNE IN MIND.

- THE RELEVANT REGULATIONS: THESE ESTABLISH THE MINIMUM CLASS TO BE USED FOR CERTAIN SURFACES DEPENDING ON THE WAY THE VIDREPUR MOSAIC IS GOING TO BE USED.
- MAINTENANCE AND CLEANING: AS A DEGREE OF ROUGHNESS HAS BEEN INCORPORATED ON TO THE MOSAIC'S SURFACE TO ENSURE THE DESIRED ANTI-SLIP LEVEL, A HIGHER LEVEL OF MAINTENANCE AND CLEANING IS ALSO NEEDED.

### PRACTICAL EXAMPLES:

BASED ON PRESENT REGULATIONS, BOTH CLASS 2 AND 3 COULD BE USED FOR A HOSPITAL'S INDOOR STAIRCASE. REGARDING MAINTENANCE AND CLEANING, CLASS 3 INVOLVES HIGHER MAINTENANCE AND CLEANING THAN CLASS 2. ANTI-SLIP LUX CLASS 2 WOULD BE IDEAL FOR THIS PURPOSE

### CLASSIFICATION OF VIDREPUR'S PRODUCTS ACCORDING TO THE RESULTS OF THE SLIP

RESISTANCE TEST (RD)	CLASS	MINIMUM CLASS REQUIRED
35<RD<=45	CLASS 2	DRY INTERIORS: SURFACES WITH A SLOPE EQUAL TO OR HIGHER THAN 6% AND STAIRCASES. INTERIORES HÚMEDAS TALES COMO TERRAZAS CUBIERTAS, VESTUARIOS, DUCHAS, BAÑOS, KITCHENS.
RD>45	CLASS 3	INTERIORES HÚMEDAS: SURFACES WITH A SLOPE EQUAL TO OR HIGHER THAN 6% AND STAIRCASES WHERE DEPTH DOES NOT EXCEDE 1,50M